



LED FLOODLIGHT SPECIFICATIONS

Descriptions	10w	20w	30w	50w	200w	500w
LED Power consumption	10w	20w	30w	50w	200w	500w
LED Initial Flux (@PW 6500K)	>f100 mm.					
Lamp Maintain Flux EFFICACY	100 lm.					
Dimensions	8.5x11x3cm	14x18x4cm	18x22x5cm	23x28x5.5cm	27x31x15.5cm	41x43x34cm
Weight	0.3 kg	0.5 kg	1.0 kg	1.3 kg	6.7 kg	
LED Source	SMD 3030					
Lamp base	Hook Ring ,Tobe,E40 Thread,Adjustabe Bracket					
Color temperature	3,000 Kelvins.[warm light]/6500 Kelvins. [Daylight] [c]					
CRI	Ra > 80					
THDi	<15%					
Power Factor	>0.9					
Flicker	No Flickering					
Beam angle	120°					
Lamp Efficiency	>90%					
IP	IP 65					
Load Type	Dimmable 0-100%[FOODLIGHT-D] / Non-Dim [FOODLIGHT-N]					
Input Voltage	85-265 VAC. (50-60 Hz.)					
Light Decay	<15% (50,000 Hours)					
Working Environment	Temp: -25~55°c / humid: 10-90%					
Material	Aluminum					
Certificate	วอน. 1955-2551					
Warrantee	2 Years					
*Option	No Option				IoT	