



มอก. 1955-2551

LED DOWNLIGHT HIGHBAY-HBH SPECIFICATIONS

Descriptions	100w	150w	200w
LED Power consumption	100w	150w	200w
LED Initial Flux (@PW 6500K)	>f130 mm.		
Lamp Maintain Flux EFFICACY	130lm		
Dimensions	W345xL345xH380	W2700xL270xH360	W360xL360xH330
Weight	3.5 Kg.	3.5 Kg.	5 Kg.
LED Source	SMD 3030		
Lamp base	Hook Ring ,Tobe,E40 Thread,Adjustabe Bracket		
Color temperature	3,000 Kelvins.[warm light]/6500 Kelvins. [Daylight] [c]		
CRI	Ra > 80		
THDi	<15%		
Power Factor	>0.9		
Flicker	No Flickering		
Beam angle	25° 60°100°		
Lamp Efficiency	>90%		
IP	IP 65		
Load Type	Dimmable 0-100%[HIGHBAY-HBH-D] / Non-Dim [HIGHBAY-HBH-N]		
Input Voltage	85-265 VAC. (50-60 Hz.)	85-305 VAC,(50 Hz)	
Light Decay	<15% (50,000 Hours)		
Working Environment	Temp: -10~45°c		
Material	Aluminum		
Certificate	มอก. 1955-2551		
Warrantee	2 Years		