



LED HIGHTBAY HBL SPECIFICATIONS

Descriptions	100w	150w	200w
LED Power consumption	100w	150w	200w
LED Initial Flux (@PW 6500K)	>f130 mm.		
Lamp Maintain Flux EFFICACY	130 lm.		
Dimensions	H317 φ270	H347 φ270	H397 φ270
Weight	2.7 kg	4.0 kg	6.6 kg
LED Source	SMD LED		
Lamp base	Hook Ring ,Tobe,E40 Thread,Adjustabe Bracket		
Color temperature	3,000 Kelvins.[warm light]/6500 Kelvins. [Daylight] [c]		
CRI	Ra > 80		
THDi	<15%		
Power Factor	>0.9		
Flicker	No Flickering		
Beam angle	60° /90°/120°		
Lamp Efficiency	>90%		
IP	IP 65		
Load Type	Dimmable 0-100%[HI-BAY-HBL-D] / Non-Dim [HI-BAY-HBL-N]		
Input Voltage	85-305 VAC. (50 Hz.)		
Light Decay	<15% (50,000 Hours)		
Working Environment	Temp: -25~55°c / humid: 10-90%		
Material	Aluminum die cast		
Certificate	วอน. 1955-2551		
Warrantee	2 Years		