



ստ. 1955-2551

LED HIGHTBAY UFO SPECIFICATIONS

Descriptions	70w	100w	200w	240w
LED Power consumption	70w	100w	200w	240w
LED Initial Flux (@PW 6500K)	140	>f130 mm.		
Lamp Maintain Flux EFFICACY	9800lm	130 lm..		
Dimensions	W25xH10.5 cm	W25xH10.5 cm	W34xH10.5 cm	W36.5xH10 cm
Weight	2.3kg	2.3 kg.	4.1kg.	5.4 kg
LED Source	SMD Philips Lumileds 3030			
Lamp base	Hook Ring ,Tobe,E40 Thread,Adjustabe Bracket			
Color temperature	3,000 Kelvins.[warm light]/6500 Kelvins. [Daylight] [c]			
CRI	Ra > 70			
THDi	<15%			
Power Factor	>0.9			
Beam angle	60° /90°/120°			
Lamp Efficiency	>90%			
IP	IP 65			
Load Type	Dimmable(Trailing Edge/Leading Edge/0-10V) [UFO-D] / Non-Dim [UFO-N]			
Input Voltage	85-305 VAC. (50 Hz.)			
Light Decay	<15% (50,000 Hours)			
Working Environment	Temp: -25~55°c / humid: 10-90%			
Material	Aluminum die cast			
Certificate	TIS. 1955-2551			
Warrantee	2 Years			
*Option	IoT			